



SUPER SINGLE DRILLING RIG

GENERAL OVERVIEW

Depth rating: 3,300ft (4-1/2" DP)
Horsepower: 360 HP
Max. Hook load 247,300 lbs

DRAWWORKS

Type: Single Drum
HP rating: 360 HP
Drilling line: 1" EIPS
Main brake: Band
Auxiliary brake: Eaton 224WCB
Drive: Caterpillar C18
Gears: 5 + Reverse



MAST (API 4F)

Type: Single open front
Height: 72 ft
Static Hook load Cap: 247,000 lbs
Wind Rating: 100 Km/Hr
Standpipe: 4"

Travelling Block

Type: UTB 110
Max. Hook load: 247,300Lbs

POWER SWIVEL

Type: Foremost (Optional)
Rating: 100 ton

PIPE HANDING SYSTEM

Type: Optional

DRILLING MODULE

Rated Load weight: 50 Tons
Turning Radius: 26ft
Axles Qty: 6
Tires: 12-20 x 18PR

SUBSTRUCTURE (API 4F)

Type: Pinned on Carrier
Clear Height: 10ft-10"
Casing load: 198,500 Lbs
Drill Floor size: 13ft-2" x 17ft-9"

ROTARY TABLE

Kelly Bushing: Pin Drive
Max. Table opening: 17-1/2"

MUD PUMPS

Type: F Series
HP rating: 500 HP (Optional)
Pressure Rating: 5,000 psi

MUD SYSTEM

Active system capacity: 400 bbls (Optional)
Shale shakers: Brandt (Optional)

WATER TANK

Capacity: Optional

FUEL TANK

Capacity: Optional

